

BS450/650/850ELCD

BS Series

Wall-Mountable UPS to
Make the Most of Your Work Space



Energy-Saving

Wall-Mountable

Surge Protection

Cable Collector

LCD Display

USB Port to PC

The BS Series UPS provide home and office user peace of mind surge protection against spikes and power abnormalities. With EMI/RFI filters eliminating line noise or disturbances, it could supply reliable backup during power interruptions, brownouts and blackouts. With the optional wall-mounted placement, it could make the most of your works place.


The included PowerPanel® Personal Edition management software showcases the feature-rich abilities such as input/output power voltage readings, self-diagnostics, and approximate battery backup time. As the GreenPower UPS™ Technology offers clean and stable battery backup, the BS Series UPS could improve the operating efficiency and eliminate the waste energy consumption.

APPLICATIONS

- Home and Home Office
- Home Theater System
- Small Office

SERIES FEATURES

- GreenPower UPS™ Technology
- EMI, RFI, Surge and Spike Protection
- Auto-Restart/Auto-Charge
- USB Connectivity Port
- User-Replaceable Batteries
- Horizontal / Wall-mounted Use
- Cable Collector Included
- PowerPanel® Personal Edition Software



Cable Collector



Energy-Saving Technology

GreenPower UPS™ Technology

The patented advanced energy-saving technology improves the UPS operating efficiency and eliminates waste energy consumption.



Powerpanel® Personal Edition

Auto-shutdown Software

Compatible with Windows 10, 8, Windows 7, Vista, XP, 2000; Windows Server 2012, 2008, 2003. Software compatible with Mac and Linux is available for download from our website.

*Software functions may vary due to firmware version and/or hardware constraints.

TECHNICAL SPECIFICATION

Model	BS450ELCD	BS650ELCD	BS850ELCD
Configuration			
Capacity (VA / Watts)	450 / 270	650 / 390	850 / 510
Energy-Saving Technology	Yes		
Input			
Frequency Range	47 Hz – 63 Hz (Auto Sensing)		
Output			
UPS Outlets (Numbers)	(6) Schuko or (6) FR or (6)UK(UK x 4+ IEC x 2) outlets		
On Battery Output Voltage	Simulated Sinewave at 230 Vac +/- 5%		
On Battery Output Frequency	50 Hz / 60 Hz +/- 1%		
Transfer Time (Typical)	4ms		
Overload Protection	On Utility: Circuit Breaker & Internal Current Limiting On Battery: Internal Current Limiting		
Surge Protection and Filtering			
Surge Protection	Yes		
DSL / Phone / FAX / Modem Protection	RJ11 / RJ45 (One In / One Out)		
Physical			
Dimensions (H x W x D) (mm)	113.6 x 271 x 160.7		
Weight (kg)	3.1	3.8	4.3
Battery			
Sealed Maintenance Free Lead Acid Battery	12V / 4.5AH x 1	12V / 7AH x 1	12V / 8.5AH x 1
User Replaceable	Yes		
Typical Recharge Time	8 Hours		
Runtimes			
Half-load / Full-load (mins)	10 / 2	11 / 3	10 / 2
Status Indicators			
Audible Alarms	On Battery, Low Battery, Overload		
Multi-function LCD Readout	Yes		
Communication			
PowerPanel® Personal Edition	Windows 8 / 7 / Vista / XP / 2000, Server 2012 / 2008 / 2003, Linux		
Management			
Auto-Charge / Auto-Restart	Yes		
Connectivity Ports	USB		

